ML280 DOT MATRIX PRINTER



ML280

9-PIN DOT MATRIX PRINTER

THE RELIABLE AND AFFORDABLE PRINTER FOR INDUSTRIAL AND POINT OF SALE APPLICATIONS

As the entry level printer in the Oki 9-pin dot matrix range, the ML280 is fast and robust, yet compact and light. A true demand document printer with bottom feed and short tear, its special size makes it ideal for customer service environments and industrial workstation applications.

MAIN FEATURES OF THE ML280 PRINTER

- Compact 80 column dot matrix printer
- Oki's unique, high durability 9-pin print head
- Multi-part continuous forms handling (original + 3 copies)
- Up to 300 characters per second print speed
- Ideal for data logging, label printing and point of sale use
- Suited to harsh environments
- DC version also available for remote or mobile use

OKI

ML280 DOT MATRIX PRINTER

PRODUCT SPECIFICATION

		ML280
General	Number of pins	9
	No. of multi-part forms	4 (one original + 3 copies)
Speed & throughput	Super speed (12cpi)	300cps
	High speed draft (10cpi)	240cps
	Utility (12cpi & 10cpi)	200cps
	Near letter quality (12cpi & 10cpi)	50cps
	Fastest print speed	300cps
Font & print features	Carriage width (10cpi)	80 columns
	Max. in compressed mode	132 columns
	Character pitch	10/12/17.1 pitch
	Graphics resolution	Up to 240 x 216 dpi
	Typeface & Font	Utility, High Speed, Draft, NLQ
	Typestyle	Emphasised, Enhanced, Double Width, Italics
Emulations & interfaces	Printer emulations	Epson FX or IBM Graphics or Oki MicroLine
	Standard interfaces	Centronics Parallel
	Optional interfaces	Serial RS 232C/RS 422/Current Loop
Paper-handling	Continuous paper	76.2 — 241.3mm
	First printable line (from top of page)	Cut sheet: 15mm Continuous: 16.9mm
	Standard	Autoload single sheet, Platen pin feed, Low tear-off, Paper end detection
	Optional	Roll paper stand, Pull tractor feed, Single bin sheet feeder
Physical	Dimensions (HxWxD)	80 x 360 x 275mm
	Weight	4.5kg
	Memory	Standard buffer 1 line
	Noise level	‹ 55dB(A)
Power	Power requirements	230V AC
	Frequency	50/60Hz
Reliability	Print head life	200 million characters
	Ribbon life	3 million characters (re-inking cartridge)
Supplies life	MTBF	6,000 hours

OKI

Only use genuine Oki Original consumables to ensure the best quality and performance from your hardware. Non Oki Original products may damage your printer's performance and invalidate your warranty. Specifications subject to change without notice. All trademarks acknowledged.

Oki, Network Solutions for a Global Society

Oki Europe, Part of Oki Electric

Oki Europe Ltd,
Central House, Balfour Road,
Hounslow, Middlesex, TW3 1HY,
United Kingdom
tel: +44 (0)20 8219 2190
fax: +44 (0)20 8219 2199
www.okieurope.com

As an ENERGY STAR Partner, Oki Europe Ltd has determined that this product meets the ENERGY STAR guidelines for energy efficiency

©2003 Oki Europe Ltd.